

# Signature VM



## The Signature VM package delivers vessel-mounted AD2CP capabilities based on present-day technology

Until now, ADCP current surveys have been complex and time-consuming processes. A successful current survey depends on highly skilled personnel and the hardware set-up is unique, and challenging, for each vessel. This leads to concerns regarding interfacing, synchronization, offsets and mounting. A miscalculation in connection with any one of these factors can lead to errors that affect the final velocity data quality.

Nortek's vessel-mounted ADCP current survey package – called Signature VM – opens up new and unprecedented opportunities to the community, while offering operational convenience and reduced complexity. Data quality can be safeguarded, and both errors and initial installation time can be substantially reduced by using an integrated system where each module is pre-qualified.

# Signature VM



## Highlights

- ✓ Five beams for current and depth
- ✓ Outstanding bottom-track performance
- ✓ A coherent system that is quick and convenient to operate

## Applications

- ✓ Coastal research
- ✓ Port and harbor mapping
- ✓ Studies of tidal currents
- ✓ Sediment transport studies

# Signature VM

## Technical specifications

### → Water velocity measurements for Signature VM1000

Profiling range*	30 m
Cell size	0.2–2 m
Max no. cells	128
Min. blanking	0.1 m
Minimum accuracy	0.3% of the measured value +/- 0.3 cm/s
Velocity resolution	0.1 cm/s
Maximum sampling rate	14 Hz
No. of beams	4 slanted at 25 degrees

\*) Maximum range depends on acoustic scattering conditions and transmit power.

### → Water velocity measurements for Signature VM500

Profiling range*	70 m
Cell size	0.5–4 m
Max no. cells	128
Min. blanking	0.5 m
Minimum accuracy	0.3% of the measured value +/- 0.3 cm/s
Velocity resolution	0.1 cm/s
Maximum sampling rate	6 Hz
No. of beams	4 slanted at 25 degrees

\*) Maximum range depends on acoustic scattering conditions and transmit power.

### → Bottom velocity measurements for Signature VM1000

Single ping std @ 3 m/s	0.5 cm/s
Long-term accuracy	± 0.1% / ± 0.1 cm/s
Minimum altitude	0.2 m
Maximum altitude	30 m

# Signature VM

## → Bottom velocity measurements for Signature VM1000

Velocity resolution	0.01 mm/s
---------------------	-----------

Maximum sampling rate	4 Hz
-----------------------	------

## → Bottom velocity measurements for Signature VM500

Single ping std @ 3 m/s	0.5 cm/s
-------------------------	----------

Long-term accuracy	$\pm 0.1\%$ / $\pm 0.1$ cm/s
--------------------	------------------------------

Minimum altitude	0.3 m
------------------	-------

Maximum altitude	70 m
------------------	------

Velocity resolution	0.01 mm/s
---------------------	-----------

Maximum sampling rate	2 Hz
-----------------------	------

## → Depth measurements for Signature VM1000

No. of beams	1 vertical
--------------	------------

Maximum sampling rate	2 Hz
-----------------------	------

Max. range	30 m
------------	------

Vertical resolution / accuracy	0.001 m / 1% of the measured value**
--------------------------------	--------------------------------------

\*\*) Assuming a constant speed of sound

## → Depth measurements for Signature VM500

No. of beams	1 vertical
--------------	------------

Maximum sampling rate	2 Hz
-----------------------	------

Max. range	70 m
------------	------

Vertical resolution / accuracy	0.001 m / 1% of the measured value**
--------------------------------	--------------------------------------

\*\*) Assuming a constant speed of sound

## → Echo intensity

Sampling	Same as velocity for slanted beams
----------	------------------------------------

Resolution	0.5 dB
------------	--------

Dynamic range	70 dB slanted beams
---------------	---------------------

No. of beams	4 slanted at 25 degrees
--------------	-------------------------

# Signature VM

## → Echo intensity

Beam width	2.9°
------------	------

## → Other

Temperature sensor range /accuracy	-4 °C to 40 °C / 0.1 °C
------------------------------------	-------------------------

Pressure	Piezo resistive
----------	-----------------

Standard range	0-100 m (inquire for options)
----------------	-------------------------------

Accuracy/precision	0.1% FS / better than 0.002% of full scale
--------------------	--

Compass and tilt	Solid-state magnetometer
------------------	--------------------------

Data recording	16 GB (inquire for options)
----------------	-----------------------------

Data cable	20 m Ethernet cable (inquire for options)
------------	---

IO	Ethernet
----	----------

DC Input	12–48 V DC
----------	------------

## → Environmental

Operating temperature	-4 °C to 40 °C
-----------------------	----------------

Storage temperature	-20 °C to 60 °C
---------------------	-----------------

Shock and vibration	IEC 60068-1 / IEC 60068-2-64
---------------------	------------------------------

EMC approval	IEC 61000
--------------	-----------

Depth rating	300 m – Bottom track is limited to surface vessels
--------------	--

Connectors	Straight fitted MCBH6F (Ethernet)
------------	-----------------------------------

Housing	Small instrument housing
---------	--------------------------

Material	POM with titanium fasteners
----------	-----------------------------

## → Rack-Mount Processing Unit

Processor/memory	Intel i7, 8 GB
------------------	----------------

Hard disk	SSD 256 GB
-----------	------------

Operating system	Windows® 10
------------------	-------------

Housing	19" rack-mountable 1 HE
---------	-------------------------

Dimensions	480x45x220 mm (19" rack-mountable 1 HE)
------------	---

Interface box with UPS	600 VA 230 V AC
------------------------	-----------------

# Signature VM

## → Rack-Mount Processing Unit

Dimensions	480x90x220 mm (19" rack-mountable 2 HE)
Total weight	10 kg (computer and UPS)
Connections	Power, Signature VM, GNSS, Ethernet, USB, HDMI, VGA
Operator control	Optional 19" rack mount
LCD panel	Optional 19" rack mount

## → Nortek Signature VM acquisition software

Acquisition	Signature VM - binary GNSS - Advanced navigation protocol
Timing	< 0.6 s, IEEE1588/PTP for absolute time stamping (GNSS/Signature VM)
Configuration	Signature VM (partly) GNSS Advanced navigation
Display	Vessel track, Vessel track in map, Bottom-track velocity, Velocities East / North, Echo amplitude, Echo correlation, Vertical depth
Status	Signature VM + GNSS
Output	NMEA data string online ASCII CSV, MATLAB and MATLAB VMT file export offline

## → GNSS Compass

Brand and model	Advanced navigation GNSS compass
Position accuracy(with dGNSS) / post-processed	Horizontal: 0.6 m / 0.01m, Vertical: 1.0 m / 0.02 m
Heading accuracy / post-processed	0.2° / 0.09°
Supported navigation systems	GPS L1, GLONASS G1, GALILEO E1, Beidou B1
Motion	9-axis IMU
Communication	Ethernet 10/100
Timing	PTP, NTP timeserver functionality
Protocol	NMEA0183 AN Packet protocol, TSS1, Simrad